

SOFRAZER

Leader in Process Viscometry

Expertise and innovation

in viscosity measurement and control

Process viscometers

Viscosity analyzers
at reference temperature

Portable and lab viscometers

OEM viscosity measurement solutions

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93



Sofraser MIVI sensor

Process viscometer with **high performance and flexibility**



The Sofraser MIVI sensor is the ideal process instrument for inline or on reactor, instant, and permanent viscosity measurement.

This established device has excellent capabilities in any fluid, diverse applications, and in various positions.

Via simple mounting plus paired and matched electronics, the Sofraser MIVI sensor suits all of your requirements.

- **High repeatability**
- **Configuration for high temperature and high pressure working conditions**
- **Approved design for explosive areas and sanitary processes**
- **Simple installation, no maintenance and non-wearing parts**
- **Varied mounting configurations and positions allow optimal fluid measure**

Specifications

Viscosity

Measuring range From 0.1-10 mPa.s to 1 000 000 mPa.s
High sensitivity 0.01-10 mPa.s

Repeatability $\pm 0.1\%$ of full scale range

Conditions

Operating temperature From -30°C to 300°C

Working pressure 60 bar, option up to 500 bar, more on request

Material

316L stainless steel
Special alloy: Hastelloy, 316Ti, Duplex, etc.
Protective coatings: Diamond-Like (ADLC), PTFE, Enamel, etc.

Safety & Hygiene Hazardous areas ATEX, FM, JIS, KGS approved
Sanitary design according to 3A

Degree of protection

IP 67
Temperature probe Internal or external



Sofraser electronic range

Viscosity and temperature processors



Sofraser has the world's largest transmitter and processor range, covering from simple data acquisition needs to complex viscosity and temperature requests. Equipped with numerous outputs possibilities, the processors can offer multi-sensor capabilities.

- **Easy to use electronics and simple mounting**
- **Constant display of the viscosity and temperature, real time control**
- **Effortless connection to any data acquisition system or process controller, up to 12 current outputs**
- **Multi-sensor option and programmable parameters up to 8 products**





Sofraser Thermoset MIVI

Powerful online viscosity analyzer at reference temperature

The Sofraser Thermoset MIVI combines the established MIVI sensor with technological viscosity measurement at reference temperature.

By drawing fluid from the process and taking it to user reference temperature, it allows a perfect viscosity measurement in correlation with ASTM D-445. Its design provides a permanent measure without a bath or oven, and absolutely no clogging.

- Reliable and repeatable measure
- Permanent process operation in one installation
- Integrated measuring chamber: very few maintenance and easy installation
- ATEX design, optional density measurement, viscosity index calculation

Specifications

Viscosity

Measuring range at reference temperature	1-100 cP, 10-1000 cP, 100-10 000 cP cSt on request with incorporated densimeter
Repeatability	±1% of full scale range

Conditions

Product inlet temperature	190°C max. - Higher on request
Reference temperature	From 40°C to 150°C, according to the requirements
Working pressure	16 bar - Higher on request
Safety	Hazardous areas ATEX



Sofraser PIVI range

Portable and lab viscometers



The Sofraser PIVI range answers the most accurate viscosity requirements in a compact and easy to use system for applications ranging from quality control to goods delivery control.

The Sofraser PIVI viscometers integrate a digital display and internal memory of 16 measures in order to optimize the polyvalence of your process controls.

- Accurate and reliable in every context
- Small sample volume
- Easy to clean and use from one application to another
- No wearing parts, low maintenance
- Compact, simple and robust

Specifications


Viscosity

Measuring range	From 0.1-100 mPa.s to 10-10 000 mPa.s
Repeatability	±0.5% of full scale range

Conditions

Sample temperature	Up to 200°C
Material	316L stainless steel
Degree of protection	IP 67
Weight	From 0.9 kg





OEM viscosity measurement solutions

Designed for process machinery

For quantity markets, Sofraser designs process viscometer features and creates specific developments to match requirements.

Through the machinery and optimization of fluid quality, our goal is to increase both manufacturers' and customers' profitability.

- **Unprecedented versatility**
- **Robust, reliable, and maintenance-free**
- **Easy-to-handle and install**



Expertise and innovation

in viscosity measurement and control

Sofraser invented and patented **the world's first vibrating viscometer at resonance frequency** and remains unsurpassed regarding process reliability and accuracy.

The active part of the sensor, a vibrating rod held in oscillation at resonance frequency, is driven by constant electrical power. The vibration amplitude varies according to the viscosity of the product in which the rod is immersed.

SOFRASER



По вопросам продажи и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес для всех регионов: srr@nt-rt.ru || www.sofraser.nt-rt.ru